

## AC607 FIRE STOP ACRYLIC SEALANT

### Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/16/2015

Revision date: 1/12/2016

Supersedes: 3/16/2015

Version: 1.0

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product form : Mixture  
Trade name : AC607 FIRE STOP ACRYLIC SEALANT  
Product code : AC607  
Type of product : Adhesives, Sealants  
Product group : Trade product

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### 1.2.1. Relevant identified uses

Intended for general public

###### 1.2.2. Uses advised against

No additional information available

##### 1.3. Details of the supplier of the safety data sheet

AKKİM YAPI KİMYASALLARI SANAYİ ve TİCARET A.Ş.  
Yeşilbayır mahallesi Şimşir sokak No:22  
34555 İSTANBUL - TURKEY  
T +90 2127711371 - F +90 2127713888  
[info@akfix.com](mailto:info@akfix.com) - [www.akfix.com](http://www.akfix.com)

##### 1.4. Emergency telephone number

Emergency number : +90 2127711371 (9:00 am - 17:00 pm GMT+2)

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixture

Reproductive toxicity, Additional category, Effects on or via lactation H362 Calculation method  
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411 Calculation method

Full text of hazard classes and H-statements : see section 16

##### Adverse physicochemical, human health and environmental effects

May cause harm to breast-fed children. Toxic to aquatic life with long lasting effects.

##### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS09

Signal word (CLP) : -

Hazardous ingredients : alkanes, C14-17, chloro, chlorinated paraffins, C14-17

Hazard statements (CLP) : H362 - May cause harm to breast-fed children  
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) : P201 - Obtain special instructions before use  
P260 - Do not breathe dust, fume, gas, mist, spray, vapours  
P263 - Avoid contact during pregnancy/while nursing  
P273 - Avoid release to the environment

## AC607 FIRE STOP ACRYLIC SEALANT Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/16/2015

Revision date: 1/12/2016

Supersedes: 3/16/2015

Version: 1.0

P308+P313 - IF exposed or concerned: Get medical advice/attention  
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking  
 Child-resistant fastening : Not applicable  
 Tactile warning : Not applicable

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
alkanes, C14-17, chloro, chlorinated paraffins, C14-17	(CAS No) 85535-85-9 (EC no) 287-477-0 (EC index no) 602-095-00-X	1 - 10	Lact., H362 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
ethanediol, ethylene glycol	(CAS No) 107-21-1 (EC no) 203-473-3 (EC index no) 603-027-00-1	1 - 5	Acute Tox. 4 (Oral), H302

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
 First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
 First-aid measures after skin contact : Wash skin with plenty of water.  
 First-aid measures after eye contact : Rinse eyes with water as a precaution.  
 First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : Repeated exposure may cause skin dryness or cracking.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray.



# AC607 FIRE STOP ACRYLIC SEALANT

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/16/2015

Revision date: 1/12/2016

Supersedes: 3/16/2015

Version: 1.0

### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Recover mechanically the product.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Obtain special instructions before use. Avoid contact during pregnancy/while nursing. Do not breathe dust/fume/gas/mist/vapours/spray.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

AC607 FIRE STOP ACRYLIC SEALANT		
EU	Local name	Ethylene glycol
EU	IOELV TWA (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	20 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	40 ppm
EU	Notes	Skin
Austria	Local name	Ethylenglykol
Austria	MAK (mg/m <sup>3</sup> )	26 mg/m <sup>3</sup>
Austria	MAK (ppm)	10 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	20 ppm
Austria	Remark (AT)	H
Belgium	Local name	Ethylèneglycol (en aérosol)
Belgium	Limit value (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	20 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	40 ppm
Belgium	Remark (BE)	D, M
Bulgaria	Local name	Етиленгликол*
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Bulgaria	OEL STEL (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
Croatia	Local name	etandiol; (Etilenglikol)
Croatia	GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Croatia	GVI (granična vrijednost izloženosti) (ppm)	20 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	40 ppm
Croatia	Naznake (HR)	K, EU* Xn
Czech Republic	Local name	Ethylenglykol
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>



# AC607 FIRE STOP ACRYLIC SEALANT

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/16/2015

Revision date: 1/12/2016

Supersedes: 3/16/2015

Version: 1.0

Czech Republic	Expoziční limity (PEL) (ppm)	20 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (NPK-P) (ppm)	39 ppm
Czech Republic	Remark (CZ)	D
Estonia	Local name	1,2-etaandiool (etüleenglükool)
Estonia	OEL TWA (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	20 ppm
Estonia	OEL STEL (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
Estonia	OEL STEL (ppm)	40 ppm
Finland	Local name	1,2-Etaanidioli
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	20 ppm
Finland	HTP-arvo (15 min)	100 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	40 ppm
France	Local name	Ethylèneglycol (vapeur)
France	VME (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
France	VME (ppm)	20 ppm
France	VLE (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
France	VLE (ppm)	40 ppm
Germany	Local name	Ethandiol
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	26 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	10 ppm
Germany	Remark (TRGS 900)	DFG,EU,H,Y
Greece	OEL TWA (mg/m <sup>3</sup> )	125 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	50 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	125 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	50 ppm
Hungary	Local name	ETILÉNGLIKOL
Hungary	AK-érték	52 mg/m <sup>3</sup>
Hungary	CK-érték	104 mg/m <sup>3</sup>
Hungary	Megjegyzések (HU)	b, i, l.
Italy	Local name	Etilen glicol
Italy	OEL TWA (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	20 ppm
Italy	OEL STEL (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
Italy	OEL STEL (ppm)	40 ppm
Latvia	Local name	Etilēnglikols, (1,2-etāndiols)
Latvia	OEL TWA (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	20 ppm
Latvia	OEL STEL (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
Latvia	OEL STEL (ppm)	40 ppm
Lithuania	Local name	Etilenglikolis (1,2-etandiolis, glikolis)
Lithuania	IPRV (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	10 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	20 ppm
Lithuania	Remark (LT)	O
Luxembourg	Local name	Ethylène-glycol
Luxembourg	OEL TWA (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Luxembourg	OEL TWA (ppm)	20 ppm
Luxembourg	OEL STEL (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
Luxembourg	OEL STEL (ppm)	40 ppm
Malta	Local name	Ethyleneglycol
Malta	OEL TWA (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Malta	OEL TWA (ppm)	20 ppm
Malta	OEL STEL (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>

## AC607 FIRE STOP ACRYLIC SEALANT Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/16/2015

Revision date: 1/12/2016

Supersedes: 3/16/2015

Version: 1.0

Malta	OEL STEL (ppm)	40 ppm
Poland	Local name	Glikol etylenowy
Poland	NDS (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Portugal	Local name	Etilenoglicol
Portugal	OEL - Ceilings (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
Romania	Local name	Etilenglicol
Romania	OEL TWA (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	20 ppm
Romania	OEL STEL (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
Romania	OEL STEL (ppm)	40 ppm
Slovenia	Local name	etandiol (glikol)
Slovenia	OEL TWA (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Slovenia	OEL TWA (ppm)	20 ppm
Slovenia	OEL STEL (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
Slovenia	OEL STEL (ppm)	40 ppm
Spain	Local name	Etilenglicol
Spain	VLA-ED (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	20 ppm
Spain	VLA-EC (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	40 ppm
Spain	Notes	Vía dérmica: (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
Sweden	Local name	Ethylene glycol
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	25 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	10 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	20 ppm
United Kingdom	Local name	Ethane-1,2-diol
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> particulate 52 mg/m <sup>3</sup> vapour
United Kingdom	WEL TWA (ppm)	20 ppm vapour
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	104 mg/m <sup>3</sup> vapour
United Kingdom	WEL STEL (ppm)	40 ppm vapour
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Switzerland	Local name	Ethylèneglicol
Switzerland	VME (mg/m <sup>3</sup> )	26 mg/m <sup>3</sup>
Switzerland	VME (ppm)	10 ppm
Switzerland	VLE (mg/m <sup>3</sup> )	52 mg/m <sup>3</sup>
Switzerland	VLE (ppm)	20 ppm
Switzerland	Remark (CH)	4x15
USA - ACGIH	Local name	Ethylene glycol
USA - ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA - ACGIH	Remark (ACGIH)	URT & eye irr

## AC607 FIRE STOP ACRYLIC SEALANT Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/16/2015

Revision date: 1/12/2016

Supersedes: 3/16/2015

Version: 1.0

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment
Environmental exposure controls	: Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Paste.
Colour	: white. Grey.
Odour	: characteristic.
Odour threshold	: No data available
pH	: 7.5 - 9
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: Not applicable
Density	: 1.55 - 1.61 g/cm <sup>3</sup>
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable

### 9.2. Other information

VOC content	: < 1 g/l
-------------	-----------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

## AC607 FIRE STOP ACRYLIC SEALANT Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/16/2015

Revision date: 1/12/2016

Supersedes: 3/16/2015

Version: 1.0

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Not classified  
pH: 7.5 - 9

Serious eye damage/irritation : Not classified  
pH: 7.5 - 9

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity	: May cause harm to breast-fed children.
-----------------------	--

Specific target organ toxicity (single exposure)	: Not classified
--	------------------

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR) : 3077

UN-No. (IMDG) : 3077

UN-No. (IATA) : 3077

UN-No. (ADN) : 3077

UN-No. (RID) : 3077

## AC607 FIRE STOP ACRYLIC SEALANT Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/16/2015

Revision date: 1/12/2016

Supersedes: 3/16/2015

Version: 1.0


### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Proper Shipping Name (IATA)	: Environmentally hazardous substance, solid, n.o.s.
Proper Shipping Name (ADN)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Proper Shipping Name (RID)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Transport document description (ADR)	: UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., 9, III, (E)
Transport document description (IMDG)	: UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., 9, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Transport document description (IATA)	: UN 3077 Environmentally hazardous substance, solid, n.o.s., 9, III, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN)	: UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., 9, III, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID)	: UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., 9, III, ENVIRONMENTALLY HAZARDOUS

### 14.3. Transport hazard class(es)


#### ADR

Transport hazard class(es) (ADR) : 9  
 Danger labels (ADR) : 9



#### IMDG

Transport hazard class(es) (IMDG) : 9  
 Danger labels (IMDG) : 9




#### IATA

Transport hazard class(es) (IATA) : 9  
 Hazard labels (IATA) : 9



#### ADN

Transport hazard class(es) (ADN) : 9  
 Danger labels (ADN) : 9





## AC607 FIRE STOP ACRYLIC SEALANT Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/16/2015


Revision date: 1/12/2016

Supersedes: 3/16/2015

Version: 1.0

### RID

Transport hazard class(es) (RID) : 9  
Danger labels (RID) : 9



### 14.4. Packing group

Packing group (ADR) : III  
Packing group (IMDG) : III  
Packing group (IATA) : III  
Packing group (ADN) : III  
Packing group (RID) : III


### 14.5. Environmental hazards

Dangerous for the environment : Yes  
Marine pollutant : Yes  
Other information : No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR) : M7  
Special provisions (ADR) : 274, 335, 601, 375  
Limited quantities (ADR) : 5kg  
Excepted quantities (ADR) : E1  
Packing instructions (ADR) : P002, IBC08, LP02, R001  
Special packing provisions (ADR) : PP12, B3  
Mixed packing provisions (ADR) : MP10  
Portable tank and bulk container instructions (ADR) : T1, BK1, BK2  
Portable tank and bulk container special provisions (ADR) : TP33  
Tank code (ADR) : SGAV, LGBV  
Vehicle for tank carriage : AT  
Transport category (ADR) : 3  
Special provisions for carriage - Packages (ADR) : V13  
Special provisions for carriage - Bulk (ADR) : VC1, VC2  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV13  
Hazard identification number (Kemler No.) : 90  
Orange plates :



Tunnel restriction code (ADR) : E  
EAC code : 2Z

#### - Transport by sea

Special provisions (IMDG) : 274, 335, 966, 967, 969  
Limited quantities (IMDG) : 5 kg  
Excepted quantities (IMDG) : E1



# AC607 FIRE STOP ACRYLIC SEALANT

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/16/2015

Revision date: 1/12/2016

Supersedes: 3/16/2015

Version: 1.0

Packing instructions (IMDG) : P002, LP02  
Special packing provisions (IMDG) : PP12  
IBC packing instructions (IMDG) : IBC08  
IBC special provisions (IMDG) : B3  
Tank instructions (IMDG) : T1, BK1, BK2, BK3  
Tank special provisions (IMDG) : TP33  
EmS-No. (Fire) : F-A  
EmS-No. (Spillage) : S-F  
Stowage category (IMDG) : A  
Stowage and handling (IMDG) : SW23  
MFAG-No : 171

### - Air transport

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y956  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 956  
PCA max net quantity (IATA) : 400kg  
CAO packing instructions (IATA) : 956  
CAO max net quantity (IATA) : 400kg  
Special provisions (IATA) : A97, A158, A179, A197  
ERG code (IATA) : 9L

### - Inland waterway transport

Classification code (ADN) : M7  
Special provisions (ADN) : 274, 335, 375, 601  
Limited quantities (ADN) : 5 kg  
Excepted quantities (ADN) : E1  
Carriage permitted (ADN) : T\* B\*\*  
Equipment required (ADN) : PP, A  
Number of blue cones/lights (ADN) : 0

### - Rail transport

Classification code (RID) : M7  
Special provisions (RID) : 274, 335, 375, 601  
Limited quantities (RID) : 5kg  
Excepted quantities (RID) : E1  
Packing instructions (RID) : P002, IBC08, LP02, R001  
Special packing provisions (RID) : PP12, B3  
Mixed packing provisions (RID) : MP10  
Portable tank and bulk container instructions (RID) : T1, BK1, BK2  
Portable tank and bulk container special provisions (RID) : TP33  
Tank codes for RID tanks (RID) : SGAV, LGBV  
Transport category (RID) : 3  
Special provisions for carriage – Packages (RID) : W13  
Special provisions for carriage – Bulk (RID) : VC1, VC2  
Special provisions for carriage - Loading, unloading and handling (RID) : CW13, CW31  
Colis express (express parcels) (RID) : CE11  
Hazard identification number (RID) : 90

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable



# AC607 FIRE STOP ACRYLIC SEALANT

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 3/16/2015

Revision date: 1/12/2016

Supersedes: 3/16/2015

Version: 1.0

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : < 1 g/l

##### 15.1.2. National regulations

###### Germany

VwVwS Annex reference : Water hazard class (WGK) 2, hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

###### Netherlands

SZW-lijst van kankerverwekkende stoffen : alkanes, C14-17, chloro, chlorinated paraffins, C14-17 is listed

SZW-lijst van mutagene stoffen : alkanes, C14-17, chloro, chlorinated paraffins, C14-17 is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : alkanes, C14-17, chloro, chlorinated paraffins, C14-17 is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

###### Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Pregnant/breastfeeding women working with the product must not be in direct contact with the product

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

### SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Lact.	Reproductive toxicity, Additional category, Effects on or via lactation
H302	Harmful if swallowed
H362	May cause harm to breast-fed children
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
EUH066	Repeated exposure may cause skin dryness or cracking

SDS EU AKFIX

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*